

# HNC324-TDRB



## FEATURES

4MP True WDR Fixed Mini Dome, Exterior with Black Housing

- 4 Megapixel (2688 x 1520) Resolution
- Full HD 4MP real-time video
- 3D DNR, True WDR, BLC
- IP67 & IK10 Rating
- PoE
- Vandal-proof
- H.265
- Black Housing

| Specifications          |  |
|-------------------------|--|
| Model Number            | HNC324-TDRB/2.8                                  |
| Image Sensor            | 1/3" progressive scan CMOS                       |
| Min. illumination       | 0.01 lux @ (F1.2, AGC ON), 0 lux with IR         |
| Shutter time            | 1/3s ~ 1/100,000s                                |
| Lens                    | F1.2, 2.8mm                                      |
| Angle adjustment        | Pan: -90° ~ 90°, tilt 0° ~ 75°, Rotation: 0-355° |
| Digital noise reduction | 3D DNR   |
| Wide dynamic range      | True WDR   |
| Day & night             | ICR  |
| Video compression       | H.264 / H.264+ / MJPEG / H.265 / H.265+          |
| Triple stream           | Yes  |
| Audio                   | N/A  |
| Alarm                   | N/A  |
| Max. image resolution   | 2688 × 1520                                      |
| Frame rate              | 30fps (2688 × 1520)                              |

| <b>Specifications</b>   |   |
|-------------------------|---|
| Image settings          | Saturation, brightness, contrast, sharpness adjustable through client software or web browser |
| BLC                     | Yes, zone configurable  |
| On Board Storage        | Micro SD slot, up to 128GB  |
| Alarm trigger           | Motion detection, tampering alarm   |
| Protocols               | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos     |
| System compatibility    | ONVIF   |
| General functionalities | User authentication, watermark  |
| Communication interface | 1 RJ45 10M / 100M Ethernet interface  |
| Operating conditions    | -30°C ~ 60°C (-22°F ~ 140°F) humidity 90% or less (non-condensing)                            |
| Power supply            | 12 VDC +/- 10%, PoE (802.3af)   |
| Power consumption       | Max, 6W   |
| Ratings                 | IP67 / IK10   |
| IR range                | Up to 90ft  |
| Dimensions              | Ø 4.4"x3.2"   |
| Weight                  | 610g (1.3 lbs)  |
| Electrical Box          | HTH-280ZJ-DM18RB  |