



HNC324-TDU



FEATURES

4MP True WDR Fixed Mini Dome With Built-in-MIC, Exterior

- 4 Megapixel (2688 x 1520) Resolution
- Full HD 4MP real-time video
- 3D DNR, True WDR, BLC
- IP67 & IK10 Rating
- PoE
- Built-in MIC
- H.265

Specifications	
Model Number	HNC324-TDU
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	4mm @ F1.2, 2.8mm optional
Angle adjustment	Pan: -90° ~ 90°, tilt 0° ~ 75°, Rotation: 0-355°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Day & night	ICR
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
Triple stream	Yes
Audio	1-ch Audio in (built-in Mic)
Alarm	N/A

Specifications	
Max. image resolution	2688×1520
Frame rate	30fps (2688×1520)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 6W
Ratings	IP67 / IK10
IR range	Up to 90ft
Dimensions	Ø 4.8"x3.6"
Weight	610g (1.3 lbs)
Electrical Box	HTH-280ZJ-DM46
Rain Shade	HTH-253ZJ-M
Wall Mount	HTH-272ZJ-120B
Pendant	HTH-271ZJ-120
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ