



HNC324G2-MB



FEATURES

4MP True WDR IR Mini Bullet Camera

- 4 Megapixel High Resolution
- Full HD 4MP Video Output
- Low Illumination
- 3D DNR; True WDR; BLC; True D/N
- IP67 Rating
- IR Range: up to 130ft
- H.265

Specifications	
Model Number	HNC324G2-MB
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR on
Shutter time	1/3s ~ 1/100,000s
Lens	2.8 mm, horizontal FOV 103°, vertical FOV 55°, diagonal FOV 122° 4 mm, horizontal FOV 84°, vertical FOV 45°, diagonal FOV 100° 6 mm, horizontal FOV 52°, vertical FOV 28°, diagonal FOV 61°
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Video compression	Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG
Max. Image Resolution	2688 x 1520
Frame rate	60Hz: 30fps (2688 × 1520, 1920 × 1080, 1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Storage	NAS, on board 128GB SD card slot.
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos

Specifications	
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 6W
Weather proof rating	IP67
IR range	UP to 130ft
Dimension	Ø70 × 161.7 mm (Ø2.76" × 6.37")
Weight	Approx. 490 g (1.1 lb.)
Electrical Box	HTH-280ZJ-XS