HNC324G2-TDB



FEATURES

4MP True WDR Fixed Mini Dome, Exterior with Grey Housing

- 4 Megapixel (2688 x 1520) Resolution
- Full HD 4MP real-time video
- 3D DNR, True WDR, BLC
- IP67 & IK10 Rating
- PoE
- Vandal-proof
- H.265
- Grey Housing

Specifications	
Model Number	HNC324G2-TDB
Image Sensor	1/3″ progressive scan CMOS
Min. illumination	0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR on
Shutter time	1/3s ~ 1/100,000s
Lens	2.8 mm, horizontal FOV 103°, vertical FOV 55°, diagonal FOV 122° 4 mm, horizontal FOV 84°, vertical FOV 45°, diagonal FOV 100°
Angle adjustment	Pan: 0° to 355°, tilt: 0° to 75°, rotate: 0° to 355°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Day & night	ICR
Video compression	Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG
Triple stream	Yes

Specifications	
Audio	N/A
Alarm	N/A
Max. image resolution	2688 × 1520
Frame rate	60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af)
Power consumption	Max, 5W
Ratings	IP67 / IK10
IR range	Up to 90ft
Dimensions	110.8 × 84.7 mm (Ø4.4″ × 3.3″)
Weight	530 g (1.2 lb.)
Electrical Box	HTH-280ZJ-DM18G
Wall Mount	HTH-272ZJ-110BG