



HNC324G2-VDZB



FEATURES

4MP VF IR Motorized Zoom, Vandal-Proof Dome With Audio, Exterior

- Full HD 1080p real-time video
- 4 Megapixel (2688 x 1520) Resolution
- IR LEDs: up to 120ft
- Supports H.265
- Support onboard storage (up to 128GB)
- IP67 & IK10
- Vandal-proof
- Motorized Zoom

Specifications	
Model Number	HNC324G2-VDZB
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR on
Shutter time	1/3s ~ 1/100,000s
Lens	2.8 ~ 12mm @ F1.6, Angle of view: 95.8° to 29.2°
Day & night	ICR
digital noise reduction	3D DNR
Wide dynamic range	120dB
Angel adjustment	Pan: 0° ~ 355°, tilt 0° ~ 75°
Video compression	Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG
Max. image resolution	2688 x 1520
Frame rate	60Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)
Audio	1/1

Specifications	
Network storage	NAS
Alarm	1/1
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark, dual stream
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Onboard storage	Built-in Micro SD slot, up to 128 GB
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af)
Power consumption	Max. 10.5W
Impact protection	IK10
Ingress protection level	IP67
IR range	Up to 130ft
Dimensions	Ø6.1" × 4.4"
Weight	880 g (1.9 lb.)
Wall Mount	HTH-473ZJ-155
Pendant Mount	HTH-471ZJ-155
Pole and Corner Mount	P:HTH-275ZJ, C:HTH-276ZJ