



HNC324G2-XDZ



FEATURES

4MP Motorized Vari-focal EXIR Turret, Exterior

- 4 Megapixel (2688 × 1520) Resolution
- Full HD 4MP real-time video
- True WDR & 3D DNR & BLC
- EXIR illuminator up to 100ft.
- IP67, IK10
- PoE
- H.265
- Third Stream (Must Enable Monitoring in VCA)
- Local Analog Output

Specifications	
Model Number	HNC324G2-XDZ
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR on
Shutter time	1/3s ~ 1/100,000s
Lens	2.8 to 12 mm, horizontal FOV 95.8° to 29.2° @ F1.6
Angle adjustment	Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°
Digital noise reduction	3D DNR
Wide Dynamic Range	True WDR, 120db
Backlight compensation	Yes, zone configurable
Video compression	Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG
Audio input output	Yes

Specifications	
Bit rate	32 Kbps ~ 8 Mbps
Dual stream	Yes
Max. image resolution	2688 x 1520
Frame rate	60Hz: 30fps (2688 × 1520, 1920 × 1080, 1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Storage	Micro SD Card up to 128 GB
Network storage	NAS
Alarm I/O	1/1
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af)
Power consumption	Max, 11W (12.5W with ICR on)
Ingress protection	IP67, IK10
EXIR range	up to 130ft
Dimensions	Ø 138.3 × 126 mm (Ø 5.4" × 5.0")
Weight	830 g (1.8 lb.)
Pendant Mount	HTH-471ZJ-135
Wall Mount	HTH-473ZJ-135
Corner Mount	HTH-276ZJ
Pole Mount	HTH-275ZJ
Junction Box	HTH-280ZJ-PT6