



HNC325-MB



FEATURES

5MP True WDR IR Mini Bullet Camera

- This model has been replaced by [HNC326-MB](#)
- 5 Megapixel High Resolution
- Full HD Video Output
- Low Illumination
- 3D DNR; True WDR; BLC
- IP67 Rating
- IR Range: up to 100ft
- True Day / Night

Specifications	
Model Number	HNC325-MB
Image Sensor	1/2.9" progressive scan CMOS
Min. illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	4mm @ F2.0 (2.8mm optional) Angle of view: 63.5° (81° for 2.8mm)
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	120dB WDR
Video compression	H.265 / H.264 / MJPEG
Max. Image Resolution	2560 x 1920
Frame rate	20fps (2560×1920), 30fps(2560×1440, 2048×1536, 1920×1080, 1280×720)

Specifications	
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Network storage	Support microSD/SDHC/SDXC card (128Gb) local storage, NAS (NFS,SMB/CIFS), ANR
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af)
Power consumption	Max 6W, PoE(802.3af, class 3), 7W
Weather proof rating	IP67
IR range	UP to 100ft
Dimension	Φ2.76" × 6.1"
Weight	0.9lbs
Electrical Box	HTH-280ZJ-XS