



HNC325-XB



FEATURES

5MP True WDR EXIR Bullet Camera

- **This model has been replaced by [HNC326-XB](#)**
- 5 Megapixel High Resolution
- Real Time 30FPS recording @ 5MP (2944 x 1656)
- Low Illumination
- 3D DNR; True WDR; BLC
- IP66 Rating
- IR Range: up to 150ft
- True Day / Night

Specifications	
Model Number	HNC325-XB
Image Sensor	1/2.9" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	4mm @ F2.0 (2.8mm optional) Angle of view: 63.5°
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide Dynamic Range	True WDR
Video compression	H.264 / H.264+ / H.265 / MJPEG
Max. Image Resolution	5MP (2944 x 1656)
Frame rate	20fps (2944×1656),30fps(2560×1440) 30fps (1920×1080)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser

Specifications	
Network storage	Support microSD/SDHC/SDXC card (128G) local storage, NAS (NFS,SMB/CIFS), ANR
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 12.5W
Weather proof rating	IP67
IR range	UP to 150ft
Dimension	Φ4.13" × 11.8"
Weight	2.65lbs
Electrical Box	HTH-260ZJ