




HNC326-VBZ



FEATURES

6MP WDR VF Motorized Zoom Bullet, Exterior

- 6 Megapixel High Resolution
- Full HD 6MP Video Output
- Low Illumination
- Support H.265
- IP67 Rating, IK10
- IR Range: up to 150ft
- True Day / Night
- Motorized Zoom

Specifications	
Model Number	HNC326-VBZ
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8 - 12mm @ F1.6
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	120dB True WDR
Video compression	H.264 / MJPEG / H.264+ / H.265 / H.265+
Max. Image Resolution	3072 x 2048
Frame rate	20fps (3072 × 2048), 30fps (2560 x 1440)
Audio	1/1

Specifications	
BLC	Yes, zone configurable
Network storage	NAS
Alarm	1/1
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Interoperability	ONVIF, PSIA, CGI
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 18W
Protection Level	IP67, IK10
IR range	UP to 150ft
Dimension	□5.67" x 13.10"
Weight	4 lbs
Electrical Box	Included with Camera
Pole,Corner	P:HTH-275ZJ,C:HTH-276ZJ