
# HNC326G2-VBZ



## FEATURES

6MP WDR VF Motorized Zoom Bullet, Exterior

- 6 Megapixel High Resolution
- Full HD 6MP Video Output
- Low Illumination
- Support H.265
- IP67 Rating, IK10
- IR Range: up to 200ft
- True Day / Night
- Motorized Zoom

| Specifications | |
|---|---|
| Model Number | HNC326G2-VBZ |
| Image Sensor | 1/2.8" Progressive Scan CMOS |
| Min. illumination | 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR |
| Shutter time | 1/3s ~ 1/100,000s |
| Lens | Varifocal lens, motorized lens, 2.8 to 12 mm |
| Day & night | IR cut filter with auto switch |
| Digital noise reduction | 3D DNR |
| Wide dynamic range | 120dB True WDR |
| Video compression | Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG |
| Max. Image Resolution | 3200 × 1800 |
| Frame rate | 60 Hz: 20 fps (3200 × 1800) 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720) |

| Specifications | |
|---|---|
| Audio | 1/1 |
| BLC | Yes, zone configurable |
| Network storage | NAS |
| Alarm | 1/1 |
| Protocols | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos |
| Interoperability | ONVIF, PSIA, CGI |
| Security | User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark |
| Communication interface | 1 RJ45 10M/ 100 M Ethernet interface |
| Operating conditions | -30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing) |
| Power supply | 12 VDC +/- 25%, PoE (802.3af) |
| Power consumption | Max, 15W |
| Protection Level | IP67, IK10 |
| IR range | UP to 200ft |
| Dimension | 308.5 mm × 97.9 mm × 93 mm (12.2" × 3.9" × 3.7") |
| Weight | Approx. 1385 g (3.1 lb.) |
| Electrical Box | Included with Camera |
| Pole,Corner | P:HTH-275ZJ,C:HTH-276ZJ |