

HNC328-XDRB



FEATURES

8MP EXIR Turret, Exterior, Grey Housing

- Black Housing
- 8 Megapixel (3840 x 2160) Resolution
- Full HD 5MP real-time video
- True WDR & 3D DNR & BLC
- EXIR illuminator up to 100ft.
- IP67
- PoE

| Specifications | |
|-------------------------|--|
| Model Number | HNC328-XDRB |
| Image Sensor | 1/2.5" progressive scan CMOS |
| Min. illumination | 0.01 lux @ F1.2, AGC ON, 0 lux with IR |
| Shutter time | 1/3s ~ 1/100,000s |
| Lens available | 2.8mm @ F1.6, angle of view: 102° 2.8-12mm |
| Angle adjustment | Pan: 0° ~ 355°, tilt 0° ~ 75° |
| Digital noise reduction | 3D DNR |
| Wide dynamic range | True WDR, 120db |
| Backlight compensation | Yes, zone configurable |
| Video compression | H.264 / MJPEG / H.264+ / H.265 |
| Bit rate | 32 Kbps ~ 16 Mbps |
| Dual stream | Yes |
| Max. image resolution | 3840 x 2160 |
| Frame rate | 15fps (3840×2160), 30fps (2944×1656)30fps(1920×1080) |

| Specifications | |
|-------------------------|---|
| Image settings | Saturation, brightness, contrast, sharpness adjustable through client software or web browser |
| Network storage | NAS |
| Alarm trigger | Motion detection, tampering alarm |
| Protocols | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos |
| System compatibility | ONVIF, PSIA, CGI |
| General functionalities | User authentication, watermark |
| Communication interface | 1 RJ45 10M/ 100 M Ethernet interface |
| Operating conditions | -30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing) |
| Power supply | 12 VDC +/- 10%, PoE (802.3af) |
| Power consumption | Max, 5W (7W with ICR on) |
| Ingress protection | IP67 |
| EXIR range | up to 100ft |
| Dimensions | Ø 127 x 97.5 mm (5"x3.8") |
| Weight | 670g (1.5 lbs) |
| Electrical Box | HTH-285ZJ-MRB |
| Wall Mount | HTH-273ZJ-130-TRLRB |