

# HNC328G2-WDA



## FEATURES

8 MP WDR Fixed, Vandal-Proof Mini Dome W/ Audio, Exterior

- Up to 8 megapixel (3840 × 2160) resolution
- Built in Mic
- True WDR & 3D DNR & BLC
- On-board storage (up to 128 GB)
- IP66 & IK08 protection
- Vandal-proof housing

Specifications	
Model Number	HNC328G2-WDA
Image sensor	1/2.8" Progressive Scan CMOS
Min. illumination	0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	2.8 mm, horizontal FOV 104.3°, vertical FOV 55.9°, diagonal FOV 123.8°
Day & night	ICR
Digital noise reduction	3D DNR
Wide Dynamic Range	True WDR, 120db
Video compression	Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG Third stream: H.265/H.264
Alarm	1/1
Audio	1/1
Max. image resolution	(3840 × 2160)

Specifications	
Frame rate	60 Hz: 20 fps (3840 × 2160) 30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception, storage error
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	Flickerless, dual stream, heartbeat, mirror, user authentication, video mask, watermark
Communication interface	1 RJ45 10M / 100M ethernet port
On-board storage	Built-in Micro SD card slot, up to 128 GB
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)
Power supply	12 VDC ± 25%, 0.54 A, max. 6.5 W
Power consumption	Max. 8W
Ingress protection level	IP66, IK08
IR range	Up to 30ft
Dimensions	Ø113.6 mm × 72.6 mm (Ø 4.5" × 2.9")
Weight	400 g (0.9 lb.)
Electric Box	HTH-280ZJ-DM46
Wall Mount	HTH-272ZJ-120B
Pendant	HTH-271ZJ-120
Corner and Pole	P:HTH-275ZJ, C:HTH-276ZJ