



HNC344-VDZ



FEATURES

4MP True WDR Smart sense Vari-Focal Motorized Dome, Exterior

- 4 Megapixel (2688 x 1520) Resolution
- Full HD 4MP real-time video
- Smart Sense
- IP67 Rating
- PoE
- Vari-Focal
- H.265

Specifications	
Model Number	HNC344-VDZ
Image Sensor	1/2.7" progressive scan CMOS
Min. illumination	0.007 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8 - 12 @ F1.4
Focus	Auto
Angle adjustment	Pan: 0° ~ 355°, tilt 0° ~ 75°, Rotation: 0 ~ 355°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Day & night	ICR
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
Triple stream	Yes
Audio	1/1
Alarm	1/1
Max. image resolution	2688×1520

Specifications	
Frame rate	30fps (2688×1520)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af, class 3)
Power consumption	Max, 11W
Ratings	IP67 & IK10
IR range	Up to 90ft
Dimensions	Ø 6"x4.4"
Weight	2 lbs
Electrical Box	HTH-280ZJ-DM55
Wall Mount	HTH-473ZJ-155
Pendant	HTH-471ZJ-155
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ