



HNC346G2P-XBLU-SL



FEATURES

6MP True WDR 24/7 Color Panoramic Turret, Exterior

- 6 Megapixel (3632x1632) Resolution
- PoE
- Full Color Night View
- H.265+
- Strobe Light With Audible Alarm
- Smart Sense
- Built In Mic and Speaker

Specifications	
Model Number	HNC346G2P-XBLU/SL
Image Sensor	2 × 1/2.5" Progressive Scan CMOS
Min. illumination	0.0005 Lux @ (F1.0, AGC ON), 0 Lux with light
Lens	Fixed focal lens, dual lens: 2.8 mm
Angle adjustment	Pan: 0° to 355°, tilt: 0° to 90°, rotate: 0° to 360°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Day & night	24/7 Color
Video compression	Main stream: H.265+/H.265/H.264+/H.264 Sub-stream: H.265/H.264/MJPEG
Audio In	Yes (built in mic)
Alarm	Audible Warning and Strobe Light
Max. image resolution	3632x1632

Specifications	
Frame rate	20 FPS (3632x1632)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Micro SD slot, up to 256GB
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Power supply	12 VDC ± 25%, 0.79 A, max. 9.5 W, Ø5.5 mm coaxial power plug, PoE: 802.3af, Class 3, 36 V to 57 V, 0.29 A to 0.18 A, max. 10.5 W
Power consumption	Max, 10.5W
Ratings	IP67
Visible Light Range	Up to 130ft
Dimensions	118.6 mm × 105.1 mm × 305.4 mm (4.7" × 4.1" × 12")
Weight	3.1 lbs
Electrical Box	HTH-260ZJ
Pole and Corner	C: HTH-276ZJ Pl:HTH-275ZJ