



HNC348-XB-L-SP



FEATURES

8MP True WDR Smart Color Bullet, Exterior

- 8 Megapixel (3840 x 2160) Resolution
- Solar Powered
- Full Color Night View
- H.265
- Battery Included.

Specifications	
Model Number	HNC348-XBLSP/2.8
Image Sensor	1/1.2" Progressive Scan CMOS
Min. illumination	0.0005 Lux @ (F1.0, AGC ON), B/W: 0 Lux with white light
Shutter time	1/3s ~ 1/100,000s
Lens	2.8mm
Angle Adjustment	Solar Cover: Pan: 0° to 358°, tilt: -40° to 40° Camera: Pan: 0° to 360° tilt: -60° to 0°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Day & night	24/7 Color with visible light
Video compression	Main stream: H.265 Sub-stream: H.265/MJPEG *Full power mode: main stream supports H.265+
Audio	N/A
Alarm	N/A
Max. image resolution	3840 × 2160
Frame rate	50 Hz: 12.5 fps (3840 × 2160, 2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 15 fps (3840 × 2160, 2688 × 1520, 1920 × 1080, 1280 × 720)

Specifications	
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Built-in 64 GB eMMC storage
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-20 °C to 60 °C (-4 °F to 131 °F). Humidity 95% or less (non-condensing)
Power supply	12 VDC \pm 20%, Ø5.5 mm coaxial power plug
Power consumption	Max, 3.2W
Ratings	IP67
Visible Light Range	Up to 90ft
Dimensions	829.9 × 696.3 × 760 mm (32.7" × 27.4" × 30") (Max. size of the camera after it is completely assembled)
Weight	25.4 kg (56.0 lb.)
Battery	Included. HTA-2FSCH30
Battery Size	236 x 154 x 80mm
Battery Voltage	10.8 V
Battery Type	Lithium
Capacity	30Ah
Battery Weight	7.3lbs