



HNC348G2P-XBLU-SL



FEATURES

8MP True WDR 24/7 Color Panoramic Bullet, Exterior

- 8 Megapixel (5120 × 1440) Resolution
- PoE
- Full Color Night View
- H.265+
- Strobe Light With Audible Alarm
- Smart Sense
- Built In Mic and Speaker

Specifications	
Model Number	HNC348G2P-XBLU/SL
Image Sensor	2 × 1/1.8" Progressive Scan CMOS
Min. illumination	0.0005 Lux @ (F1.0, AGC ON), 0 Lux with light
Lens	Fixed focal lens, dual lens: 4 mm
Angle adjustment	Pan: 0° to 355°, tilt: 0° to 90°, rotate: 0° to 360°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Day & night	24/7 Color
Video compression	Main stream: H.265+/H.265/H.264+/H.264 Sub-stream: H.265/H.264/MJPEG
Audio In	Yes (built in mic)
Alarm	Audible Warning and Strobe Light
Max. image resolution	5120 × 1440

Specifications	
Frame rate	When WDR is On: 50 Hz: 12.5 fps (5120 × 1440) 60 Hz: 15 fps (5120 × 1440) When WDR is Off: 50 Hz: 20 fps (5120 × 1440) 60 Hz: 20 fps (5120 × 1440)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Micro SD slot, up to 256GB
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Power supply	12 VDC ± 25%, 0.88 A, max. 10.5 W, Ø 5.5 mm coaxial power plug, PoE: IEEE 802.3af, Class 3, 36 V to 57 V, 0.35 A to 0.22 A, max. 12.5 W
Power consumption	Max, 12.5W
Ratings	IP67
Visible Light Range	Up to 130ft
Dimensions	118.6 mm × 105.1 mm × 305.4 mm (4.7" × 4.1" × 12")
Weight	3.1 lbs
Electrical Box	HTH-260ZJ
Pole and Corner	P:HTH-275ZJ, C:HTH-276ZJ