



HNC354G2-TD



FEATURES

4MP True WDR Smart sense Fixed Mini Dome, Exterior

- 4 Megapixel (2688 x 1520) Resolution
- Full HD 4MP real-time video
- Smart Sense
- IP67 & IK10 Rating
- PoE
- Vandal-proof
- H.265
- Face Capture
- Third Stream (Must Enable Monitoring in VCA)

Specifications	
Model Number	HNC354G2-TD
Image Sensor	1/3" Progressive Scan CMOS
Min. illumination	0.003 lux @ (F1.4, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8mm @ F1.4
Angle adjustment	Pan: 0° ~ 355°, tilt 0° ~ 75°, Rotation: 0 ~ 355°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Day & night	ICR
Video compression	Main stream: H.265/H.264/H.265+/H.264+ Sub-stream: H.265/H.264/MJPEG
Triple stream	Yes
Audio	N/A
Alarm	N/A
Max. image resolution	2688×1520

Specifications	
Frame rate	60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 50°C (-22°F ~ 122°F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af, class 3)
Power consumption	Max, 6.5W
Ratings	IP67 / IK10
IR range	Up to 90ft
Dimensions	121.4 mm × 92.2 mm (Ø 4.8" × 3.6")
Weight	580 g (1.3 lb.)
Electrical Box	HTH-280ZJ-DM46
Wall Mount	HTH-253ZJ-M with HTH-272ZJ-120B
Pendant	HTH-271ZJ-120 with HTH-253ZJ-M
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ