HNC354G2-XBAUSL



FEATURES

4MP True WDR Smart sense Strobe Light Bullet with built-in Speaker, Exterior

- 4 Megapixel (2688 x 1520) Resolution
- Full HD 4MP real-time video
- Smart Sense
- IP67 Rating
- PoE
- Strobe Light With Built In Speaker
- H.265

Specifications	
Model Number	HNC354G2-XBAU/SL
Image Sensor	1/3" Progressive Scan CMOS
Min. illumination	0.003 Lux @ (F1.4, AGC ON), B/W: 0 Lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	Fixed focal lens, 2.8, 4, and 6 mm optional
Focus	Auto
Angle adjustment	Pan: 0° ~ 360°, tilt 0° ~ 90°, Rotation: 0 ~ 360°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Day & night	ICR
Video compression	Main stream: H.265/H.264/H.265+/H.264+ Sub-stream: H.265/H.264/MJPEG
Triple stream	Yes
Audio	0/1, talk through built-in speaker
Alarm	Audible Warning and Strobe Light
Max. image resolution	2688×1520
Frame rate	60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes

Specifications	
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af, class 3)
Power consumption	Max, 12W
Ratings	IP66
IR range	Up to 240ft
Dimensions	Ø 105 mm × 287.6 mm (Ø 4.1" × 11.3")
Weight	1135 g (2.5 lb.)
Electrical Box	HTH-260ZJ
Wall Mount	N/A
Pendant	N/A
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ