HNC354G2-XDU



FEATURES

4MP True WDR Smart sense Fixed Turret, Exterior

- 4 Megapixel (2688 x 1520) Resolution
- Full HD 4MP real-time video
- Smart Sense
- IP67 Rating
- Third Stream (Must turn off VCA function)
- Face Capture
- H.265
- Built in Mic

Specifications	
Model Number	HNC354G2-XDU
Image Sensor	1/2.7" Progressive Scan CMOS
Min. illumination	0.003 Lux @ (F1.4, AGC ON), B/W: 0 Lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	Fixed focal lens, 2.8mm
Angle adjustment	Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°
Lens Type and FOV	2.8 mm, horizontal FOV 103°, vertical FOV 55°, diagonal FOV 123°
Wide dynamic range	True WDR 120dB
Day & night	ICR
Video compression	Mainstream: H.265/H.264/H.265+/H.264+ Sub-stream: H.265/H.264/MJPEGThird-stream: H.265 / H.264 (Third-stream must have VCA functions turned off)
Triple stream	Yes
Audio	1ch input. built-in-mic
Alarm	N/A
Max. image resolution	2688×1520
Frame rate	60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)

Specifications	
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Tampering alarm, network disconnected, IP address conflict, illegal login
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 50°C (-22°F ~ 122°F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af, class 3)
Power consumption	Max, 6.8W
Ratings	IP67
IR range	Up to 100ft
Dimensions	Ø 138.3 mm × 126.3 mm (Ø 5.4" × 5.0")
Weight	730 g (1.6 lb.)
Electrical Box	HTH-280ZJ-DM21
Wall Mount	HTH-273ZJ-140B
Pendant Mount	HTH-271ZJ-140
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ