



HNC512-VBZ118



FEATURES

4 MP 25 × IR Varifocal Bullet Network Camera

- Audio support (microphone not included)
- 4 Megapixel (2560 × 1440) Resolution
- Full HD 2560 × 1440 60fps recording
- True WDR & 3D DNR & BLC
- Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
- IP67
- IR Range 200m
- 25X optical zoom lens 4.7 to 118 mm

Specifications	
Model Number	HNC512-VBZ118
Image Sensor	1/2.5" Progressive Scan CMOS
Min. illumination	0.009 Lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter time	1 s to 1/30,000 s
Lens	4.7 to 118 mm
Day & night	ICR
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Backlight compensation	Yes, zone configurable
Video compression	Main stream: H.265+/H.265/H.264+/H.264 Sub-stream/Fourth stream/Fifth stream: H.265/H.264/MJPEG Third stream: H.265/H.264
H.265 compression profile	Main profile
Bit rate	32 Kbps ~ 8 Mbps

Specifications	
Dual stream	Yes
Max. image resolution	2688 × 1520
Frame rate	60 fps (2560 × 1440, 1920 × 1080, 1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
On board Storage	Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
Audio	1/1
Alarm	1/1
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
IR Range	Up to 200m
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 90% or less (non-condensing)
Power supply	12 VDC ± 20%, PoE (802.3at)
Power consumption	Max. 18W
Ingress protection	IP67
Dimensions	144.1 mm × 375.2 mm (Ø 5.7" × 14.8")
Weight	2130g (4.7 lbs)
Electrical Box	HTH-260ZJ (included with camera)
Pole	HTH-275ZJ
Corner	HTH-276ZJ