

# HNC6986F-H



## FEATURES

### 8MP Panoramic Dome Camera

- 1/1.8" Progressive Scan CMOS
- Up to 8 Megapixel (4096 × 1800) High Resolution
- 8MP Real-time Video
- Day / Night
- Audio 1/1 and Alarm 1/1
- Image stitching adjustment
- IP66 Outdoor

Specifications	
Model Number	HNC6986F-H
Image Sensor	1/1.8" progressive scan CMOS
Min. illumination	0.002 lux@F2.2, AGC ON
Shutter time	1/25s ~ 1/100,000s
Lens	5mm X 4, Pan: 180°, Tilt: 78.4°
Angle adjustment	Pan: 0° ~ 360°, Tilt 45° ~ 90°
Day & night	IR Cut filter
Video compression	H.264 /H.265/ MJPEG
Bit rate	32 Kbps ~ 16 Mbps
Max, image resolution	4096 × 1800
Frame rate	(4096 × 1800) 25/30fps
Network storage	NAS, ANR
System compatibility	ONVIF, PSIA, ISAPI

<b>Specifications</b>	
Communication interface	1 RJ45 10M / 100M / 1000M Ethernet port and 1 RS-485 interface
WDR	DWDR
On-board storage	Built-in SD slot, up to 128 GB
Audio	1/1
Alarm	1/1
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	DC 12V, AC 24V +/- 10%, PoE (802.3af)
Power consumption	22W
Dimensions	Ø 7.67" x 6.26"
Weight	2850g (6.28 lbs)
Wall Mount	HTH-605ZJ-DM30