HNC6D24-IZS



FEATURES

EXIR Flexible PanoVu Network Camera

- 30fps @ 1920 x 1080
- H.265, H.265+, H.264, H.264+
- 30 to 90ft IR Range
- IP67, IK10
- 4 Flexible Lens
- 6 behavior analysis, 4 exception detection, and face detection

Specifications	
Model Number	HNC6D24-IZS
Image Sensor	1/2.7″ Progressive Scan CMOS
Min. Illumination	Color: 0.006 Lux @ (F1.2, AGC ON), 0.01 Lux @ (F1.6, AGC ON) B/W: 0.002 Lux @ (F1.2, AGC ON); 0.003 Lux @ (F1.6, AGC ON) 0 Lux with IR on
Shutter Speed	1 – 1/100,000s
Auto-iris	N/A
Day & Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	120 dB
3-Axis Adjustment	Four flexible lens in one track, slide range: -180° to 180°, tilt: 0° to 135°, rotate: 0° to 355°
Focal Length	2.8mm – 12mm
Aperture	F1.6
FOV	Horizontal field of view: 30° to 96.3° Vertical field of view: 17° to 54° Diagonal field of view: 34° to 121°
IR Range	30ft to 90ft

Specifications	
Wave Length	850nm
Video Compression	Main stream: H.265+/H.265/H.264+/H.264 Sub stream: H.265/H.264/MJPEG Third stream: H.265/H.264
H.264 Type	Baseline Profile/Main Profile/High Profile
H.264+	Support
H.265 Type	Main Profile
H.265+	Support
Video Bit Rate	32 Kbps to 16 Mbps
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM/AAC
Audio Bit Rate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)/16-64Kbps(AAC)
Behavior Analysis	Line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection
Exception Detection	Audio exception detection, scene change detection, defocus detection
Max. Resolution	1920 × 1080
Frame Rate	Main stream 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720) Sub-stream 50Hz: 25fps (704 × 576, 640 × 480) 60Hz: 30fps (704 × 480, 640 × 480) Third stream 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480)
Image Enhancement	BLC, 3D DNR, EIS
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness, and white balance are adjustable by client software or web browser
Day/Night Switch	Day/Night/Auto/Schedule/Triggered by Alarm In
SVC	H.264 Support
Network Storage	Support Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR
Alarm Trigger	Motion detection, video tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP
General Function	One-key reset, anti-flicker, mirror, heartbeat, password protection, privacy mask, watermark, IP address filter
API	ONVIF (PROFILE S, PROFILE G), ISAPI
Simultaneous Live View	Up to 20 channels
User/Host	Up to 32 users 3 levels: Administrator, Operator and User
Audio I/O	1-ch 3.5 mm input (line in/Mic in), 1-ch 3.5mm output, dual-track, stereo
Alarm I/O	2 input, 2 output (up to 24 VD, 1A or 110 VAC, 500mA)
On Board Storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
Communication Interface	1 RJ45 10M/100M/1000M Ethernet port 1 RS-485 interface
Material	Aluminum alloy, engineering plastics
Protection Level	IK10, IP67
Power Supply	12VDC, PoE
Power Consumption	Max. 17W
Working Temperature	-30 °C to 60 °C (-22 °F to 140 °F). -H: -40 °C to 60 °C (-40 °F to 140 °F) Humidity 95% or less (non-condensing)
Dimensions	Ø11.42″ × 5.73″
Weight	10.3lbs
Wall Mount	HTH-602ZJ

Specifications	
Pendant Mount	HTH-661ZJ, HTH-662ZJ
Pole Mount	HTH-275ZJ
Corner	HTH-276ZJ