

# HNC6D52G0-IHS



## FEATURES

### 5MP Dual-Directional PanoVu Camera

- High quality imaging with 5 MP resolution
- 3D DNR technology delivers clean and sharp images
- Efficient H.265 compression technology
- Built-in microphone for real-time audio security

Specifications	
Model Number	HNC6D52G0-IHS
Image Sensor	1/2.7" Progressive Scan CMOS
Min. illumination	Color: 0.009 Lux @ (F1.6, AGC ON), B/W: 0.0018 Lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter time	1s to 1/100,000 s
Lens	2.8 mm
Angle adjustment	P: -90 to 90°; T: 0 to 60° (2.8mm)
Digital noise reduction	3D DNR
Wide dynamic range	120dB
Day & night	Day, Night, Auto, Schedule, Triggered by Alarm In
Video compression	Main Stream: 50Hz: 25fps ((2560 × 1920, 2048 × 1536); 60Hz: 30fps (2560 × 1920, 2048 × 1536)Sub Stream: 50Hz: 25fps (640 × 480, 704 × 576); 60Hz: 30fps (640 × 480, 704 × 480)
Triple stream	Yes
Audio	2 built-in mics, 1 line in, 1 line out
Alarm	1 input, 1 output (max. 36 VDC, 30mA)
Max. image resolution	2560 × 1920
Frame rate	60Hz: 30fps (2560 × 1920, 2048 × 1536)

Specifications	
Image settings	Rotate, saturation, brightness, contrast, sharpness, white balance adjustable by client software or web browser *Rotate and perimeter protection events (line crossing detection, intrusion detection, region entrance detection, region exiting detection) cannot be enabled at the same time
BLC	Yes, zone configurable
On Board Storage	Micro SD slot, up to 256GB
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, SFTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS
System compatibility	ONVIF, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-40° to 60°, humidity 95% or less (non-condensing)
Power supply	12 VDC, POE (802.3af)
Power consumption	Max, 11W
Ratings	IP67 / IK10
IR range	Up to 90ft
Dimensions	164.3 × 84.6 × 67.4 mm (6.5" × 3.3" × 2.7")
Weight	770g (1.7 lb.)
Electrical Box	HTH-280ZJ-DE7
Wall Mount	HTH-270ZJ-DE7