



HNP114-IR-4X



FEATURES

4MP Indoor Network Mini PTZ Dome Camera

- 2560 x 1440
- 4X Optical Zoom
- 120dB WDR
- 12VDC, PoE
- IP66, IK10
- 60ft IR

Specifications	
Model Number	HNP114-IR/4X
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	Color: 0.005 Lux @(F1.6, AGC ON) B/W:0.001 Lux @(F1.6, AGC ON) 0 Lux with IR
Max Resolution	2560 x 1440
Image Compression	Main Stream: H.265+/H.265/H.264+/H.264 Sub-stream: H.265/H.264/MJPEG
Focal Length	2.8 - 12mm, 4X
Shutter Time	1s to 1/30,000 s
Digital Zoom	32X
Angle of View	69.5° - 26.48°
Aperture	F1.6 - F2.7
WDR	120dB
Pan & Tilt Range	Pan: 0 - 330°, Tilt : 0 - 90°
Number of Presets	300
Patrol	N/A
D/N Mode	ICR
Park Action	Preset

Specifications	
Alarm I/O	2/2
Audio I/O	1/1
Frame Rate	50Hz: 25fps (2560 × 1440, 2048 × 1536, 1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 24fps (2560 × 1440), 30fps(2048 × 1536, 1920 × 1080, 1280 × 960, 1280 × 720)
Protection Level	IP66, TVS 4,000V lightning protection, surge protection and voltage transient protection
Wall Mount	HTH-294ZJ-PT
Power	12VDC, PoE+ (802.3at, class 4), Max. 18W
Dimensions	□5.15" x 4"
Weight	1.17lbs