

HNR-HD04G-DISCONTINUED



FEATURES

4 Channel Real Time HD H.264 Digital Video Recorder 120fps@1080P

- Support 4 Channels HD-SDI DVR
- Up to 120 fps Recording Speed
- Dual-stream with Adjustable fps and Resolution
- Gigabit LAN/uPnP/HD Monitoring
- Quick & Easy Network Setup
- Smart Phone Viewer Featuring Monitoring/VOD/Event Search/ Popup Message Notification
- Support iPhone, Android Mobile Client software

Specifications	
Model Number	HNR-HD04G
Operating System	Embedded Linux
Video Input (BNC, 1Vp-p)	4
Video Output	1 HDMI, 1 VGA, 1 COMPOSITE
Spot Output	N/A
Loop Out (BNC, 1Vp-p)	N/A
Live Displays	1,4
Playback Displays	1,4
Video Compression	H.264/MJPEG
Live Display Speed	120fps at 1080P
Record Resolution	1080P, 720P
Record Speed	120fps at 1080P

Specifications	
Alarm In/Out (Relay)	4 alarm input, 1 relay output
Emergency Record Mode	Yes
System Control	Key Buttons, Remote Client, IR Remote, HKB-400, Mouse Controlled GUI
System Control SW	CMS, Mac Viewer, MMS, Web (IE)
PTZ Control	RS485, Virtual Joy-Stick Control on screen by Mouse
Audio	4ch Input, 1ch Output
Display	Brightness, Contrast and Covert Feature
Text Insertion (POS)	RS232
Recording Mode	Continuous, Schedule, Sensor-Activated, Motion Detection, Event (Pre/Post), Manual (Emergency)
Recording Quality	1080P/ 720P
Pre/Post Recording	Yes
Motion Detection	Yes
Search Mode	Time Bar, Date & Time, Event/Search
Playback Modes	Forward, Reverse, Pause, 1x, 2x, 4x, 8x, 16x, 32x, 64x, x128
Multiplex Function	Simultaneous Live Display, Playback, Record, Remote Monitoring/Playback
Alarm Notification	Automatic E-mail, Network Event
Support IPFR	Intelligent Power Failure Recovery
Watermark	Yes
Password Protection	Yes
Interface	1 Ethernet, 3 USB, RS-485, RJ45, e-Sata (8 & 16 Channel Only)
Storage	2 Internal HDD
Maximum Storage	6TB
Storage Extension	eSata (8&16 Channels only)
Back Up	USB, Network, DVD Optional
Network	LAN, WAN(xDSL), DHCP, ARP, ICMP, PPPoE, UDP, TCP/IP
Remote Client	CMS, Mac Viewer, MMS, Web (IE)
3G Communication	iPhone / Android / Blackberry / Symbian / MS Mobile
Power Adapter & Consumption	12VDC, 7Amp
Operation Temperature	5°C ~ +40°C (41°F ~ 104°F)
Storage Temperature	-25°C~ +70°C (-13°F ~ 158°F)
Operation Humidity	20~80%RH Below
Storage Humidity	20~80%RH Below
Dimension	14.96in(W) x 14.17in(D) x 2.6in(H)