HNR30P4-4



FEATURES

×

4 Ch & 4 POE Network Video Recorder

- This model has been replaced by HNR32P4-4
- Up to 4-Ch IP cameras input
- 20Mbps Bit rate Input Max
- Third-party network cameras supported
- Up to 3MP resolution recording
- HDMI and VGA output at up to 1920x1080P resoluton
- Plug & Play with 4 independent PoE network interfaces
- 2 SATA HDD interface up to 6TB each

Specifications	
Model Number	HNR30P4-4
Video Compression	H.264
IP Video Input	4 ch IP with Integrated 4 port 802.3af PoE Switch (20 Mbps Bit Rate Input Max)
Video Output	1 ch HDMI, 1 ch VGA
Audio Input/Output	1/1
Two-way Audio	1/1
Real-time recording resolution	30fps @ Up to 3 Megapixels
HDMI Output Resolution	Up to 1080P/60Hz
VGA Output Resolution	Up to 1080P/60Hz
Synchronous Playback	4 ch 720P, 2 ch 1080P, 1 ch 5MP
Network Interface	1, RJ45 10M/100M/1000M
PoE Network Interfaces/Built-in switch	4 independent 100 Mbps PoE network interfaces

Specifications	
Internal SATA	2 SATA interfaces (up to 6TB each)
eSATA	N/A
USB interface	2 USB2.0
Operation Temperature	-10 °C ~ +55 °C
Chassis	19-inch 1U
Dimensions (W \times D \times H)	17.5″W x 11.4″D x 1.77″H
Weight	6.4lbs (without hard disk)