


HNR30P8-16



MB-149 效果图

FEATURES

16 Ch & 8 POE Network Video Recorder

- **This model has been replaced by [HNR32P6-16](#)**
- Up to 16 Ch IP cameras input
- 80Mbps Bit rate Input Max
- Third-party network cameras supported
- Up to 5MP resolution recording (HNC105-ZD and HNC105-VB only) Does not support 4MP cameras.
- HDMI and VGA output at up to 1920x1080P resolution
- Plug & Play with 4 independent PoE network interfaces
- 2 SATA HDD interface up to 6TB each

Specifications	
Model Number	HNR30P8-16
Video Compression	H.264
IP Video Input	16 ch IP with Integrated 8-port 802.3af PoE Switch (80 Mbps Bit Rate Input Max)
Video Output	1 HDMI, 1 VGA
Audio Input/Output	1/1
Two-way Audio	1/1
Real-time recording resolution	30fps @ Up to 5 Megapixels
HDMI Output Resolution	Up to 1080P/60Hz
VGA Output Resolution	Up to 1080P/60Hz
Synchronous Playback	8 ch
Network Interface	1, RJ45 10M/100M/1000M adaptive Ethernet Interface

Specifications	
PoE Network Interfaces/Built-in switch	8 independent 100 Mbps PoE network interfaces
Internal SATA	2 SATA interfaces (up to 6TB each)
eSATA	N/A
USB interface	2 USB2.0
Operation Temperature	-10 °C ~ +55 °C
Chassis	19-inch 1U
Dimensions (W × D × H)	17.5"W × 11.42"D × 1.77"H
Power Supply	100 ~ 240VAC
Weight	≤ 6.4 lbs (without hard disk)