



HNR32P4-4



FEATURES

4 Channel & 4 POE Network Video Recorder

- Up to 4Ch. IP cameras input
- 40 Mbps Bit rate input max and 80 Mbps Bit rate output max
- Third-party network cameras supported
- Up to 8MP resolution recording
- VGA output up to 1080p@60Hz, HDMI output up to 4K@30Hz
- 1 SATA HDD interface up to 12TB each

Specifications	
Model Number	HNR32P4-4
Video Compression	H.264 / H.264+ / H.265 / MPEG4
IP Video Input	4 Ch. (40Mbps Max input)
Video Output	1 HDMI, 1 VGA
Audio Input/Output	1/1
Two-way Audio	1/1
Real-time recording resolution	Up to 8 Megapixels
HDMI Output Resolution	4K, 3840×2160@30Hz, 1920×1080@60Hz, 1600×1200@60Hz, 1280×1024@60Hz, 1280×720@60Hz, 1024×768@60Hz
VGA Output Resolution	1920×1080@60Hz, 1280×1024@60Hz, 1280×720@60Hz, 1024×768@60Hz
Synchronous Playback	4 ch @ 1080P
Network Interface	1 RJ45 10M/100M

Specifications	
PoE Network Interfaces/Built-in switch	4 port 802.3af PoE Switch 4 independent 100 Mbps PoE network interfaces
Internal SATA	1 SATA interfaces (up to 12TB each)
eSATA	N/A
USB interface	2 x USB2.0
Operation Temperature	-10 °C ~ +55 °C
Chassis	1U
Dimension	12.4"W x 9.1"D x 1.8"H
Power Supply	48VDC, 10W
Weight	2.6 lbs (without hard disk)