



HNR32P8-8



FEATURES

8 Channel & 8 POE Network Video Recorder

- Up to 8Ch. IP cameras input
- 80 Mbps Bit rate Input Max and 160 Mbps Bit rate Output Max
- Third-party network cameras supported
- Up to 12MP resolution recording
- Independent VGA and HDMI output
- VGA output up to 1080p@60Hz, HDMI output up to 4K@30Hz
- 2 SATA HDD interface up to 12TB each

Specifications	
Model Number	HNR32P8-8
Video Compression	H.264 / H.264+ / H.265 / MPEG4
IP Video Input	8 Ch. (80 Mbps Max input)
Video Output	1 HDMI, 1 VGA
Audio Input/Output	1/1
Two-way Audio	1/1
Real-time recording resolution	Up to 12 Megapixels
HDMI Output Resolution	4K, 3840×2160@30Hz, - 2K 2560×1440@60Hz, 1920×1080@60Hz, 1600×1200@60Hz, 1280×1024@60Hz, 1280×720@60Hz, 1024×768@60Hz
VGA Output Resolution	1920×1080@60Hz, 1280×1024@60Hz, 1280×720@60Hz, 1024×768@60Hz
Synchronous Playback	8-ch, (2-ch @ 4K, or 8-ch @ 1080p)

Specifications	
Network Interface	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
PoE Network Interfaces/Built-in switch	8 independent 10/100 Mbps PoE network interfaces
Internal SATA	2 SATA interfaces (up to 12TB each)
Alarm I/O	4/1
USB interface	1 x USB2.0 and 1 x USB 3.0
Operation Temperature	-10 °C ~ +55 °C / -50°F ~ +131°F
Chassis	380mm 1U chassis
Dimension	15.2"W x 12.4"D x 2.0"H
Power Supply	100 ~ 240VAC
Power Consumption	Max. 15W
Weight	6.6 lbs (without hard disk)