

HNR50P6-16



FEATURES

16 Ch & 16 PoE Network Video Recorder

- **This model has been replaced by [HNR51P6-16](#)**
- Up to 16 Ch IP cameras input
- 100 Mbps Bit rate Input Max and 240Mbps Bit Rate Output Max
- Third-party network cameras supported
- Up to 5MP resolution recording
- HDMI and VGA output at up to 1920x1080P resolution
- Plug & Play with 16 independent PoE network interfaces
- 4 SATA HDD interface up to 6TB each

Specifications	
Model Number	HNR50P6-16
Video Compression	H.264
IP Video Input	16 ch IPC with Integrated 16 port 802.3af PoE Switch (100Mbps incoming Bandwidth)
Video Output	1 HDMI, 1 VGA, 1 BNC
Audio Input/Output	1/2
Two-way Audio	1/1
Real-time recording resolution	30fps @ Up to 5 Megapixels
HDMI Output Resolution	Up to 1080P/60Hz
VGA Output Resolution	Up to 1080P/60Hz
RAID	N/A
Synchronous	16 ch
Alarm Input/ Output	16/4

Specifications	
Network Interface	1, RJ45 10M/100M/1000M adaptive Ethernet Interface
PoE Network Interfaces/Built-in switch	16 independent 100 Mbps PoE network interfaces
Internal SATA	4 SATA interfaces (up to 6TB each)
eSATA	1 eSATA
USB interface	3, USB2.0
Chassis	19-inch rack-mounted 2U
Dimensions (W × D × H)	17.5 × 15.4 × 2.75 inch
Power Supply	100 ~ 240VAC, 6.3A
Weight	≤ 8.82 lbs (without hard disk)