

HPE-0518



FEATURES

16 Port Gigabit Unmanaged POE Switch

- Layer 2 network switch designed for video data transmission
- 16 x 10/100/1000 Mbps ethernet ports, 1 x 10/100/1000 Mbps uplink ethernet port and 1 x 10/100/1000 Mbps uplink SFP port
- IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z network standards available
- IEEE 802.3 af & at high POE power supply
- Store-and-forward switching
- Safe and reliable using 6 KV high surge protection
- Plug and play ensures simplicity and convenience.

Specifications	
Model Number	HPE-0518
Ports	16 x 10/100/1000M RJ45, 1 x 10/100/1000M RJ45 uplink, 1 x 10/100/1000M uplink SFP port
Performance	MAC Address Table: 8K Transmission Method: Store and Forward
PoE Standard	IEEE 802.3af, IEEE802.3at
Switching Capacity	36 Gbps
PoE on each Port	30W max.
PoE Power Pin	End-span: 1/2(-), 3/6(+)
Surge Protection	6KV
Power Input	Input: 100-240VAC, 50~60Hz, 230W
Dimensions	8.7" x 17.3" x 1.7"
Weight	7.78lbs
EMC	FCC (ANSI C63.4, 47 CFR PART 15B); CE-EMC/RCM (EN 55032: 2015+A11:2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1:2019, EN 50130-4:2011+A1:2014, EN 55035:2017+A11:2020); IC (ICES-003: Issue 11)
Safety	UL (UL 62368-1); CB/RCM (IEC 62368-1:2014); CE-LVD (EN 62368-1:2014+A11:2021)
Certifications	CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2010)