



HTA-PW802



FEATURES

8-port FE PoE + 2-port GE Switch HTA-PW802

- HTA-PW802 is supporting up to 30W on each LAN port if its port DIP switch is ON
- Two 10/100/1000M (UTP) are used to connect with other edge switch or NVR as uplink ports

Specifications	
Model Number	HTA-PW802
Standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3z 1000BaseTX, IEEE 802.3x Flow Control, IEEE 802.3at/af, midspan PoE compliant
Features	MAC Address: 8K, Buffer Memory: 512KB, Transmission Method: Store and Forward
Filtering/Forwarding Rates	1000Mbps port - 1,488,000pps 100Mbps port - 148,800pps 10Mbps port - 14,880pps
Transmission Media	10BaseT Cat. 3, 4, 5 UTP/STP, 100BaseTX Cat. 5 UTP/STP, 1000BaseTX Cat. 5 UTP/STP
PoE on each Port	30W max.
Output PoE Pin	4,5,7,8
LED Indicators	Power, LAN1~18 port, PoE 1~16 port
Power Input	Input: 100-240VAC, 50~60Hz, 120W or 250W
Dimensions	480 × 118 × 44 mm (L x W x H) with holder
Box Weight	2.7 kg
Operating Temperature	0 to 50°C

Specifications	
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class A, CE