



HTC-11G29DNR



FEATURES

1/3" High Resolution CCD Color DSP, 580TVL 2.9mm Corner Vandal Proof Dome camera

- Vandal resistance
- Day / Night Feature
- 580 TVL w/ 0.05 Lux
- Corner Mount w/ optional Heater
- AC 24V / DC 12V, Dual Voltage

Specifications	
Model Number	HTC-11G29DNR
Pick Up Device	CCD Image Sensor 1/3"
Horizontal Resolution	580 TVL
Synchronization Frequency	NTSC:15.734 KHz /60 Hz PAL:15.625 KHz/50 Hz
V. Frequency	NTSC (EIA): 60Hz PAL (CCIR): 50Hz
Scanning System	2:1 Interlace
Sensitivity	0.05 LUX @ F1.4
Synchronization	Line Lock (VBS)/AC type
S/N Ratio	More Than 48 dB (AGC Off)
Electronic Shutter	Up to 1/10,000 sec. (Linear)
Gamma	0.45
Video Output	1 Vp-p, 75 Ohms Composite
Mount Lens	3.6mm F=2.0 Optional Lens: 4.0mm, 6.0mm, 8.0mm, 12.0mm
Power Supply	24VAC / 12VDC / Dual Voltage

Specifications	
Power Consumption	250mA
Auto Gain Control	Automatic
White Balance	Auto Tracing White Balance
Back Light Compensation	Automatic
Fixation	3 Screws
Weight	740g
Storage Temperature	-30°C~+60°C
Operating Temperature	-10°C~+45°C