



HTC-21636V24



FEATURES

1/3" High Resolution B/W CCD Camera, 580TVL 3.6mm Board Camera

- Digital control of BLC
- Auto White Balance
- 1H mode of H.V. aperture correction
- Digital process of color matrix
- Electronic Shutter up to 1/100,000

| Specifications | |
|---------------------------|--|
| Model Number | HTC-21636V24 |
| Pick Up Device | CCD Image Sensor 1/3" |
| Image Size H * V mm | 6.0 * 4.96 |
| Picture Elements | NTSC: 711H * 494V PAL: 753H * 582V |
| Horizontal Resolution | More Than 580 TV Lines |
| Synchronization Frequency | NTSC:15.734 KHz /60 Hz PAL:15.625 KHz / 50 Hz |
| V. Frequency | NTSC (EIA): 60Hz PAL (CCIR): 50Hz |
| Scanning System | 2:1 Interlace |
| Sensitivity | 0.1 Lux F=1.4 |
| Synchronization | L.L (VBS) /AC type |
| S/N Ratio | More Than 48 dB (AGC Off) |
| Electronic Shutter | Up to 1/10,000 sec. (Linear) |

| Specifications | |
|-------------------------|---------------------------|
| Gamma | 0.45 |
| Video Output | 1 Vp-p, 75 Ohms Composite |
| Mount Lens | 3.6mm |
| Power Supply | 24VAC |
| Auto Gain Control | Automatic |
| Back Light Compensation | Automatic |
| Weight | 380g |
| Storage Temperature | -30°C to + 60°C |
| Operation Temperature | -10°C to + 45°C |