



HTC-2H6



FEATURES

1/3" High Resolution low light CCD Color DSP, 580TVL 12VDC Board Camera

- Full digital process of BLC
- Auto White Balance
- 2H mode of H.V. aperture correction
- Digital process of color matrix
- Electronic Shutter up to 1/10,000

Specifications	
Model Number	HTC-2H6
Pick Up Device	1/3" CCD Sensor
Image Size H * V mm	3.64 * 4.82
Picture Elements	NTSC:512H *492V PAL:512H * 582 V
Horizontal Resolution	580 TV Lines
Horizontal Frequency	NTSC:15.734 KHz PAL:15.625 KHz
Vertical Frequency	NTSC:60Hz PAL:50Hz
Scanning System	2:1 Interlace
Sensitivity	0.05 Lux F=1.4
Sync. System	Internal
S/N Ratio	More Than 46dB (AGC Off)
Electronic Shutter	Up To 1/100,000 sec. (Linear)

Specifications	
White Balance	Auto White Balance
Gamma Correction	0.45
Lens	3.6mm
Optional Fixed Lens	1.7mm, 2.5mm, 2.9mm, 3.6mm, 4.0mm, 6.0mm, 8.0mm,12.0mm, 16.0mm
Metal Case	N/A
Flickless Function	Yes (Optional)
Back Light Compensation	Automatic
Video Output	1 Vpp,75 Ohms Composite
Auto Gain Control	Automatic
Power Supply	12V DC (+/-10%)
Power Consumption	240mA for 12V DC
Weight	100g
Dimensions (two fold)	42*42 mm*2
Storage Temperature	-30°C to + 60°C
Operation Temperature	-10°C to + 45°C