



HTC-T78G



FEATURES

WDR Ultra Low Light 700TVL Box Cameras

- OSD function control
- Day and Night function: Auto switch from Color to B/W
- 700 TVL
- Adjustable function: Wide Dynamic Range, Back light compensation, Gain control, White Balance, Digital Slow Shutter
- Low speed shutter up to 32X
- Internal / Line Lock
- Dual Voltage: DC 12V / AC 24V

Specifications	
Model Number	HTC-T78G
Pick Up Device	1/3"Sony Super HAD CCD
Picture Elements (Pixel)	NTSC: 768H x 494V
H. Sync. Frequency	NTSC:15.734 KHz/60 Hz PAL:15.625 KHz/50 Hz
V. Sync. Frequency	NTSC: 59.94 Hz PAL: 50 Hz
Synchronization	AC: Line Lock, DC Internal
Sensitivity D/N	0.15 Lux (Color), 0.03 Lux (B/W), 0.01 Lux (Sense Up x 256)
Day/Night	Normal image, D/N with digital slow shutter
IR Ray	Sensitive IR wave 850~940nm
Wide Dynamic	High Speed, automatic 5-level exposure control for each pixel
Dynamic Range	120dB Max., 101dB typical
Auto White Balance Range	Single-push and manual, 2000K ~ 11000K

Specifications	
Resolution	700 TVL
Back Light Compensation	ON/OFF switchable
Sense-Up (Slow Shutter)	Off, x2, x4, x8, x16, x32
Gain Control	High/Medium/Custom/Low
Mount Lens	C or CS mount
Video Output	1VP-P, 75 Ohms
S/N Ratio	More than 48 dB
Power Supply	Dual Power DC 12V/AC 24V
Power Consumption	160mA at DC 12V, 250mA at AC 24V
Dimensions	107.9 x 82.6 x 76.2 mm (4.25 x 3.25 x 3 inch)
Weight	1.15 lbs
Storage Temperature	-10°C~+50°C
Operation Temperature	-10°C~+50°C