

# HTD2617-V1-3



## FEATURES

2MP Thermal and Optical Network Bullet Camera [dt\_divider style="thin" /] **This model has been replaced by the [HTD2617/PA-3](#)**

- 2 Megapixel (1920 x 1080) Resolution
- Duel Lens Module, Thermal and Optical
- Leading image processing technology: Adaptive AGC, DDE, 3D DNR, NETD less than 40 mk (@25°C, F#=1.1)
- Reliable temperature exception alarm function
- Advanced fire detection algorithm
- IP66
- Bi-spectrum image fusion, picture in picture preview

Thermal Module	
Model Number	HTD2617/V1-3
Image Sensor	Vanadium Oxide Uncooled Focal Plane Arrays
Max Resolution	160 x 120
Pixel Interval	17µm
Response Waveband	8µm to 14µm
NETD	less than 40 mk (@25°C, F#=1.1)
Lens	3.1 mm
MRAD	5.48 mrad
Field View	50° x 37.2° (H x V)
Min. Focus Distance	0.2 m
Aperture	F1.1
Optical Module	
Image Sensor	1/2.8" Progressive Scan CMOS
Max. image resolution	1920 x 1080
Min Illumination	0.002 Lux @ F1.5
Shutter Speed	1s to 1/100,000s

<b>Thermal Module</b>	
Lens	4mm
Field of View	87° x 46.2° (H x V)
WDR	DWDR
Day & Night	IR cut filter with auto switch
Bi-spectrum Image Fusion	Fusion view of the thermal view and overlaid details of the optical channel
Picture in Picture	Combines details of thermal and optical image PIP, overlay thermal image on optical image
Temperature Measurements	3 temperature measurement rule types, 21 rules (10 points, 10 areas, and 1 line)
Temperature Range	-20°C to 150°C (-4°F to 302°F)
Temperature Accuracy	± 8 °C (± 14.4 °F)
Fire detection	Dynamic fire point detection, up to 10 fire points detectable.
IR Range	120ft.
Alarm I/O	2/2
Alarm Action	SD recording/Relay output/Smart capture/FTP upload/Email linkage
Audio Input	1 3.5mm Mic in/Line in interface. Line input: 2-2.4V[p-p], output impedance:1KΩ±10%
Audio Output	Linear Level; Impedance: 600Ω
Analog Video Output	1.0V [p-p]/75Ω, PAL/NTSC/BNC
Power	12 VDC± 20% PoE (802.3af, class 4)
Power Consumption	Max. 12 W
Working Temperature/Humidity	-40 °C to 60 °C (-40 °F to 140 °F), 90% or less
Protection Level	IP66 Standard TVS 6000V Lightning protection, surge protection, voltage transient protection
Dimensions	13.9" × 4.5" × 4.5 "
Weight	3.3lbs