



HTP-T13MG



FEATURES

1.3 MegaPixel Box Camera

- 1.3 Megapixel 1.3
- Multi Streams up to 30fps @ 1280 x 1024
- Support Dual-codec (H.264 & MJPEG) simultaneously
- Web-based viewer (Internet Explorer)
- Video bit rate: 32kbps ~ 8Mbps
- Intelligent bit rate control
- SNR (Super Noise Reduction) technology
- PoE (Power over Ethernet) 802.3af
- Support bi-directional audio
- 1 Sensor inputs (Dry contact) and 1 digital outputs (TTL Level)
- Support Static or Dynamic IP for xDSL and Cable-Modem user
- Compatible with our HNVS-04 video server
- Support WESP SDK for SI and project manager
- FCC, CE, MIC, RoHS approved

Specifications	
Model Number	HTP-T13MG
Network Interface	Ethernet 10/100Base-T (RJ-45)
Network Protocol	TCP/IP, UDP, Multicast, DHCP, SMTP, HTTP, SNMP, RTP, RTSP
Image Device	Sony 1/3", 1.3M CCD (Progressive Scan)
Lens	C / CS Mount
Slow Shutter	On / Off
Mechanical Iris Lens	Fixed Iris Lens / DC Iris Lens

Specifications	
Zoom Preset	15 Presets
MIN. Illuminance	Color : 2.2 Lux, Night : 1.8 Lux (B/W) @ 50 IRE
MAX. Slow Frame	0~8 FPS Selectable
Iris	Auto / Manual
Shutter Speed	x128 ~ 1/120000 sec
AGC	Auto / Indoor / Outdoor
White Balance	Normal / High / Off
BLC	On / Off
Flickerless	Disable / 50Hz / 60Hz Selectable
Backlight Function	Disable / Fixed Window / Automatic / Histogram Integral Mode
Brightness	0~40 Adjustable
MAX. AGC Gain	0~30 Adjustable
Digital Day & Night	On / Off
Night->Day Transition	0~42 Adjustable
Day->Night Transition	0~42 Adjustable
DC Iris Lens Control Volume	0~16 Adjustable
AWB Mode	ATW Mode / PUSH Mode / Manual Mode
R/B Gain	1024~16384 Adjustable
Algorithm	G.711u
Resolution	(13 Resolution Mode Selectable)
Frame Rate	1 FPS ~ 30 FPS Selectable
Bit Rate	64K BPS
Output	Line-Out(Mini-Stereo, Single Mono) : 1 EA
Sample Rate	8K Hz
Input	Line-In(Mini-Stereo, Single Mono) : 1 EA
Port	RS-485 : 1 Port
Baud Rate	2,400 BPS ~ 115,200 BPS Selectable
Sensor Input	1 Input (Normal Open Contact)
Alarm Output	1 Output (Normal Open Contact)
Operation Temperature	-10°C~50°C / 14°F~122°F
Storage Temperature	-10°C~55°C
Operation Humidity	30%~80%, free of condensation
Storage Humidity	93% below, free of condensation
POE (802.3af)	
DC Adaptor	Input: AC 110~220V / Output: DC 12V 0.5A
Power Consumption	Max. 6W (DC12V), 7W(PoE)
Dimension (W x D x H)	65(W) x 59(H) x 109(L) [mm] / 2.6(W) x 2.3(H) x 4.3(L) [Inch]