



HTP-T1MG28H



FEATURES

HTP-T1MG28H is a 1.0 MegaPixel Bullet IP Camera with 24pcs IR LED and 3.3~12mm auto iris IR correct lens. 60ft. IR range. 30fps@1280X800. Multi Streaming (H.264, MPEG4, JMPEG)capable of recording resolution 1280X800. POE (Power over Ethernet) 802.3af or alternate DC 12V for power.

- 1.0 Megapixel IR Bullet Outdoor IP Camera
- Multi Streams up to 30fps @ 1280X800
- 3.3~12mm auto iris, ICR, 24 IR, 850nm, 60ft. IR range, 0 Lux
- 2 way MIC in, Audio out
- Web-based viewer (Internet Explorer)
- Video bit rate: 32kbps ~ 8Mbps
- Intelligent bit rate control
- DC12V, PoE802.3af
- Network: Ethernet 10/100 Mbps/RJ45
- Vandal resistance, weather resistance
- ONVIF Compliant

Specifications	
Model Number	HTP-T1MG28H
Network Interface	Ethernet 10/100Base-T (RJ45)
Network Protocol	TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, Upnp, Bonjour, RTP, RTSP, Onvif
Image Device	1 / 4
Vandal / Weather Resistance	Yes
Focal Length	3.3~12mm
Lens Driver	

Specifications	
MIN. Illuminance	0 Lux IR on
IR Illuminator	24
IR Range	60 ft.
Max Resolution	1280 x 800
H.264 / MPEG4 / MJPEG	30fps@H.264, 15fps@MPEG4, 30@MJPEG
Audio	G.711u/AMR
Audio Stream	2 way MIC in, Audio out
Sensor	1 sensor input, 1 relay output
ICR	ICR
Local Storage	SD/SDHC Slot Max 32G, 12V 1A
Power	12VDC, PoE 802.3af
Dimension (Inch)	4.64H x 4.5Ø
Weight (lbs)	3.5
Certificate	Rohs, CE, Onvif, ?IP 66