HTP-T2MG10Z



FEATURES

2.0 MegaPixel Box Camera with a 10x Optical Zoom

- 2.0 Megapixel Network IR Bullect Outdoor Camera
- Multi Streams up to 60fps @ 720p, 30fps @ 1080p
- 3.3mm-12mm, F1.4
- Two way audio, MIC in/Audio out, SD/SDHC local storage
- External I/O: Alarm in Relay out
- Web-based viewer (Internet Explorer)
- Video bit rate: 32kbps ~ 8Mbps
- Intelligent bit rate control
- PoE (Power over Ethernet) 802.3af
- Network: Ethernet 10/100 Mbps/RJ45
- ONVIF Compliant

Specifications	
Model Number	HTP-T2M10Z
Network Interface	Ethernet 10/100Base-T (RJ-45)
Network Protocol	TCP/IP, UDP, Multicast, DHCP, SMTP, HTTP, SNMP, RTP, RTSP
Image Device	1 / 2.5” CMOS (Progress Scan)
Lens Diameter	1 / 3.6”
Focal Length	F1.8 ~ F2.2 / f=4.5mm ~ 45.0mm
Zoom	X10 Optical Zoom and X10 Digital Zoom
Zoom Preset	15 Presets
MIN. Illuminance	Color : 2.2 Lux, Night : 1.8 Lux (B/W) @ 50 IRE

Specifications	
Motion Image Stabilizer	On / Off
BLC	On / Off
Image Flip	Vertical Flip (On/Off) / Horizontal Flip (On/Off)
Flickerless	On / Off
Metering	Center-Weighted / Spot / Evaluation
Exposure Mode	Manual / Auto / Aperture Priority / Shutter Speed Priority
Brightness	-2.0 EV ~ 2.0 EV
Focus Range	Full / Normal
Zoom Tracking	On / Off
White Balance Index	Auto / Indoor / Outdoor
Image Sharpness	High / Middle / Low
Digital Noise Reduction	High / Middle / Low / Off
Chroma CR/CB	High / Middle / Low
Hue CR/CB	-2.0 ~+2.0
Algorithm	G.711u
Resolution	(18 Resolution Modes Selectable)
Frame Rate	1 FPS ~ 30 FPS Selectable
Bit Rate	64K BPS
Output	Line-Out(Mini-Stereo, Single Mono) : 1 EA
Sample Rate	8K Hz
Input	Line-In(Mini-Stereo, Single Mono) : 1 EA
Port	RS-485 : 1 Port
Baud Rate	2,400 BPS ~ 115,200 BPS Selectable
Sensor Input	1 Input (Normal Open Contact)
Alarm Output	1 Output (Normal Open Contact)
Operation Temperature	-10°C~50°C / 14°F~122°F
Storage Temperature	-10°C~55°C
Operation Humidity	30%~80%, free of condensation
Storage Humidity	93% below, free of condensation
POE (802.3af)	
DC Adaptor	Input: AC 110~220V / Output: DC 12V 0.5A
Power Consumption	Max. 6W (DC12V), 7W(PoE)
Dimension (W x D x H)	64.5(W) x 69.5(H) x 133.1(L) [mm] / 2.6(W) x 2.8(H) x 5.3(L) [Inch]
Weight	512g / 1.1 lbs (Without a Bracket)