



HTP-T3MG



FEATURES

3.0 MegaPixel POE Box IP Camera.

- 3.0 Megapixel Network D/N Box Camera
- Multi Streams up to 30fps @1080p, 20Fps @ 3M
- C/CS mount, ICR, 0.5 Lux
- Two way audio, MIC in / Audio out, SD/SDHC local storage
- External I / O: Alarm in Relay out
- Web-based viewer (Internet Explorer)
- PVideo bit rate: 32kbps ~ 8 Mbps
- Interlligent bit rate control
- ONVIF Compliant
- PoE or 12VDC

Specifications	
Model Number	HTP-T3MG
Description	3 Megapixel pixel Network Camera
IR LED	NA
Sensor	1/2.5
Processor	DSP Base (DaVinci TM320DM368)
Lens	CS mount Lens
Min. Illumination	0.5 Lux / F1.4
SNR (signal noise ratio)	50dB
Video Compression	H.264 HP/MP/BP, MPEG-4 SP, M-JPEG

Specifications	
Resolution	QXGA (2048 x 1536): 20 fps, 1080p (1920 x 1080): 30 fps, 960p (1280 x 960): 30 fps, 720p (1280 x 720): 30fps, D1 (720 x 480): 30fps, VGA (640 x 480): 30fps, QVGA (320 x 240): 30 fps, QCIF (176 x 144): 30fps
Muti-streaming	Yes
ICR	Option
SD/SDHC Interface	Yes
PoE (IEEE802.3af)	Yes
Audio Support	Two-way
Alarm Input / Output	2 x D/I, 1 x D/O
ONVIF	Yes
Protocol	TCP/IP, IPV6/V4, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, HTTPS, Samba, PPPoE, UPnP, Bonjour, RTP, RTSP, RTCP
QoS	Yes
Muti-level User Access	Yes
IP Filtering	Yes
3GPP Standard	Yes
Time Management	Manual Time Setting / Time Server and NTP support / Real Time Clock
Event Management	Recording Video file to SD Card by schedule
System Management	64-ch Management Software (ExpressView)
Operation Temperature	0 °C ~ 50 °C
Certificate	CE, FCC
Size	130 mm (D) x 72 mm (W) x 58 mm (H)
Weight (gw)	400
Package	Accessories: Power Supply; Packaging (white box); CD