



HTZ-1000ISWBH



FEATURES

(Day/Night) Outdoor High Speed Dome Cameras With IR Filter 12X

- 1/4" Interline Transfer CCD
- Resolution 540TVL
- Zoom: 12x, Optical: 12x Digital
- Focal Length: F1.6 ~ 2.0, f = 3.6 ~ 44.3mm
- Min Illuminance: 0.7 Lux (Day); 0.02 Lux (Night)
- Communication: RS485
- Protocol: Pelco-D, Pelco-P Selectable
- Wall Mount Bracket
- Vandal Resistance, weather resistance
- Built-in Fan and Heater
- Power: AC 24V / 1.5A

Specifications	
Model Number	HTZ-1000ISWBH
Image Device	1/4" Interline Transfer CCD
Total Pixel	410K Pixels [811(H) x 508(V)]
Effective Pixel	380K Pixels [768(H) x 494(V)]
H. Resolution	540 TV Lines
S/N Ratio	50dB (AGC Off)
Zoom	12X Optical Zoom and 12X Digital Zoom
Focal Length	F1.6 ~ 2.0, f=3.6 ~ 44.3mm
MIN. Illuminance	0.7 Lux (Day)/0.02 Lux (Night, DSS)@50 IRE

Specifications	
Day&Night	Auto/Day/Night (IR Cut Filter)
Focus	Auto/Manual /Semi-Auto
Iris	Auto/Manual
White Balance	Auto/Manual (R&G Gain Adjustable)
BLC	On/Off
Pan / Tilt Range	Pan: 360°(Endless)/Tilt: 90°
Pan/Tilt Speed	Preset: 360°/sec
Preset	128 Presets with Labels / Independent Preset Characteristic Setup
Pattern	4 Patterns (Approx. 5 Minutes for Each Pattern)
Swing	8 Swings
Group	8 Groups (MAX. 20 Entries for Each Group)
Other Functions	Auto Flip, Auto Parking, Power-up Action & etc.
Communication	RS-485
Protocol	Pelco-D, Pelco-P Selectable
Sensor In/Out	Built-in 4 Input
OSD	English On/Off
Power	24VAC
Dimension	Dome: ø 115 mm/4.5"; Housing: 150(ø)´ 146(H) mm/5.9" (ø)´ 5.7" (H)
Weight	Approx. 1 Kg / 2.2 Lbs
Operating Temp.	0°C~40°C/32°F~104°F