HTZ-2700IC



FEATURES

(Day/Night) Indoor High Speed Dome Cameras With IR Filter 27X

- 1/4″ SONY EXview CCD
- Resolution 540TVL
- Zoom: 27X Optical; 12X Digital
- F1.6~2.9, f=3.5(Wide)~94.5 (Tele) mm
- Min illuminance: 0.4 Lux (Day): 0.02 Lux (Night)
- communication: RS485
- Protocol: Peloc-D, Pelco-P Selectable
- Vandal Resistance
- Built-in Fan and Heater
- Power: AC 24V / 1.5A

Specifications	
Model Number	HTZ-2700IC
Day/Night Filter	Built-In Auto/Day/Night (IR Cut Filter)
Pick Up Device	1/4″ SONY EXview CCD
Zoom Module	Samsung Module
Communication Bus	RS485 Bus
Communication Transmission Speed	2400/4800/9600bps
Horizontal Rotation Speed	0.4°-280°(1-64 grade shift gears)
Horizontal Rotation Range	360° continuous rotation
Tilt Rotation Range	90°
Auto Flip	Rotates 180° when camera tilts to the vertical position

Specifications	
Auto zoom Speed Control	Control speed auto-adjusted according to zoom length changing
Swing	8 Swings
Group	8 Groups (MAX. 20 Entries for Each Group)
Patten	4 Patten (Approx. 5 Minutes for Each Pattern)
Other Function	Auto Flip, Auto Parking, Power-up Action
Protocol	Pelco-D, Pelco-P selectable
Sensor In/Out	Built-in 4 Input/2 Output
2 Points Scan	Yes
2 Points Scan Speed	1-64 grade available
Dwell Time(2 Points Scan)	1-60s available
Preset Positions	128 positions
Running to Preset Speed	1-64 grade available, 0.4º-280º
Dwell Time at Preset Position	1-60s available
Masking Feature	Yes
Cruise Points Qty per Cruise Group	16 preset positions
Sync	Internal/External
Scan	2:1 Interlace
Resolution	540 lines
Minimum Illumination	Day: 0.4 Lux / Night: 0.02 Lux
Zoom	27x Optical Zoom and 12x Digital Zoom
AE Mode	Auto/Iris/Shutter/Manual/Brightness
White Balance	Auto/Manual (Red & Blue Gain Adjustable)
Iris	Auto/Manual
Focus	Auto /Manual/Semi-Auto
Zoom	Auto/Manual
Focal Length	F1.6~2.9, f=3.5(Wide)~94.5 (Tele) mm
Angle of View	47°(wide), 2°(Tele-)
Backlight Compensation	On/Off
Flicker-less	On/Off
Gain	Auto
Signal	PAL/NTSC
S/N Ratio	>50dB
Video Signal Output	1.0±0.2Vp-p
Power Supply	AC24V±5%
Power Consumption	20W
Storage Temperature	-30°C~+60°C
Operating Temperature	-10°C~+45°C
Day/Night Filter	Build In