



# HTZ-2700WBH



## FEATURES

27x Optical Day/Night w/ Wall mount PTZ Cameras

- 1/4" SONY EXview CCD
- Resolution: 540TVL
- Zoom: 27X Optial; 12X Digital
- Focal Length: F1.6~2.9, f=3.5(Wide)~94.5 (Tele) mm
- Min Illuminance: 1.0 Lux (Day); 0.01 Lux (Night)
- Communication: RS485
- Protocol: Pelco-D, Pelco-P Selectable
- Vandal Resistance, weather resistance
- Built-in Fan and Heater
- Wall Mount Bracket
- Power: AC24V / 1.5A

| Specifications                   |                                         |
|----------------------------------|-----------------------------------------|
| Model Number                     | HTZ-2700WBH                             |
| Day/Night Filter                 | Built-In Auto/Day/Night (IR Cut Filter) |
| Pick Up Device                   | 1/4" SONY EXview CCD                    |
| Zoom Module                      | Samsung Module                          |
| Communication Bus                | RS485 Bus                               |
| Communication Transmission Speed | 2400/4800/9600bps                       |
| Horizontal Rotation Speed        | 0.4° - 280°(1-64 grade shift gears)     |
| Horizontal Rotation Range        | 360° continuous rotation                |
| Tilt Rotation Range              | 90°                                     |

| Specifications                     |                                                         |
|------------------------------------|---------------------------------------------------------|
| Auto Flip                          | Rotates 180° when camera tilts to the vertical position |
| Auto Zoom Speed Control            | Auto Zoom Speed Control                                 |
| Swing                              | 8 Swings                                                |
| 8 Swings                           | 8 Groups ( MAX. 20 Entries for Each Group)              |
| Patten                             | 4 Patten (Approx. 5 Minutes for Each Pattern)           |
| Other Function                     | Auto Flip, Auto Parking, Power-up Action                |
| Protocol                           | Pelco-D, Pelco-P selectable                             |
| Sensor In/Out                      | Built-in 4 Input/2 Output                               |
| 2 Points Scan                      | Yes                                                     |
| 2 Points Scan Speed                | 1-64 grade available                                    |
| Dwell Time(2 Points Scan)          | 1-60s available                                         |
| Preset Positions                   | 128 positions                                           |
| Running to Preset Speed            | 1-64 grade available, 0.4°- 280°                        |
| Dwell Time at Preset Position      | 1-60s available                                         |
| Masking Feature                    | Yes                                                     |
| Cruise Points Qty per Cruise Group | 16 preset positions                                     |
| Sync                               | Internal/External                                       |
| Scan                               | 2:1 Interlace                                           |
| Resolution                         | 540 TVL                                                 |
| Minimum Illumination               | Day: 1.0 Lux / Night: 0.01 Lux                          |
| Zoom                               | 27x Optical Zoom and 12x Digital Zoom                   |
| AE Mode                            | Auto/Iris/Shutter/Manual/Brightness                     |
| White Balance                      | Auto/Manual (Red & Blue Gain Adjustable)                |
| Iris                               | Auto/Manual                                             |
| Focus                              | Auto/Manual/Semi-Auto                                   |
| Focal Length                       | F1.6~2.9, f=3.5(Wide)~94.5 (Tele) mm                    |
| Angle of View                      | 47°(wide), 2°(Tele-)                                    |
| Backlight Compensation             | On/Off                                                  |
| Flicker-less                       | On/Off                                                  |
| Gain                               | Auto                                                    |
| Signal                             | PAL/NTSC                                                |
| Power Supply                       | AC24V±5%                                                |
| Power Consumption                  | 20W                                                     |
| Storage Temperature                | -30°C~+60°C                                             |
| Operating Temperature              | -10°C~+45°C                                             |