



HVRM-HDC400F-PD



FEATURES

4ch HD-SDI Real-time with PoC(Power over Coax) Standalone DVR

- 4ch HD-SDI Standalone DVR
- The World's First HDcctv Certified PoC/CoC 4ch HD-SDI DVR (TBD)
- Self-power supply to all 4 cameras by PoC (Power over Cable) function
- Control all 4 cameras by CoC (Control over Coax) function
- Doubles the video transmission distance by DoubleReach technology
- Max. 120/100fps Recording & Playback at Full-HD 1080p resolution
- Adjustable recording quality and framerate per each channel
- Supports High-resolutions over 1200TV lines at Live/Playback
- Supports Dual Codec(H.264,JPEG) & Multi Stream (HD, nHD(640×360))
- Full-HD 1920×1080 resolution output via HDMI port Various Live and Playback display (1/4 Split-screen)
- Robust IPFR (Intelligent Power Failure Recovery) DVR File System
- Max. 1 Internal SATA Type HDDs
- Supports Max. 16TB(e-SATA) external storage interface
- Date/Time, Calendar, Event, Thumbnail, Smart, Text Search available
- At-the-PC Playback of removed DVR HDD
- Lightning arrester on HD-SDI, RS-485, DIO ports
- Provides bundle CMS program, managing Max. 1,024 DVRs in various ways such as E-map, Viewset
- Java Viewer for Chrome, Firefox, Safari
- Supports various mobile platform (iPhone/Android Viewer, Mobile page)
- Provides Full SDK for easy and powerful customization

Specifications	
Model Number	HVRM-HDC400F-PD
Video input standard	SMPTE 292M (HD-SDI)
Resolution / framerate	SMPTE 274M (1080p, 1920×1080) : 25, 30, 29.97 FPS
Connectors	4ch, 75Ω BNC connector
PoC	4ch, Power over Coax, Max. 16 W/ch, Total 64W
Connectors	4ch, Control over Coax, Max. 57,600bps
Video output	HDMI
Live Displays	1, 4 split-screen
Compression	H.264 / JPEG
Resolution	1920×1080
Rate	120/100 fps at 1080p
Quality	1080p, 10 levels up to 12Mbps
Mode	Manual & Event / Schedule & Event / Continuous & Event
Schedule	24hrs / 7days
Mode	Instant playback / search
Speed	Max. 120/100 fps at 1080p
Search type	Time, Calendar, Timeline, Event, Thumbnail, Smart, Tex
Block playback	24hours ~ 99days
Event source	MD(Motion Detection), sensor, text, Video Loss
Event check schedule	24hrs / 7days
Event action	Buzzer, Relay, E-mail, FTP, Alarm pop-up
MD area	15×10
Sensor input	Dry contact (NO or NC selectable)
Text input	POS/ATM support, AVE VSI Pro/Hydra support
Alarm source	HDD fail, HDD almost full, Fan fail, Password fail, WRS fail
Alarm action	Warning message, Buzzer, E-mail, Relay
Input/output	Input 4ch RCA / output HDMI, RCA
Compression	16KHz, 16bit sampling ADPCM
Direction	Both
Protocols	35 models including C1080, C1080PT-Z20, Pelco-D, Pelco-P, Samsung, Panasonic and others
Interface	1 Gigabit Ethernet (10/100/1000Mbps)
Type	Static IP, Dynamic IP, xDSL
DDNS	WNS, DynDNS, NoIP, WRS
Bandwidth limit	Supported
NTP	Server / Client / Both
Users	10 monitoring, 2 playback
Streaming	1 HD, H.264 stream, Same as recording setting 1 additional H.264 stream, nHD(640 x 360) 1 JPEG stream, nHD(640 x 360) for e-mail or mobile
User level	1 admin, 10 users
User privilege	Menu, PTZ, Relay, Playback, Power, Copy, Network MIC

Specifications	
IP filtering	Supported
Storage devices	1 internal SATA HDDs, 1 external eSATA Interface,
File system	Proprietary file system, data-loss protection against power-failure
Capacity	Max. 16TB with eSATA
Backup type	Multi-channel or Single channel avi file
Backup device	USB drive (2 ports)
S.M.A.R.T.	Temperature and Health checking
Serial port	1 RS-232C, 2 RS-485
Sensor input	4 Dry-contact
Relay output	2 Relay
Device	Front panel, IR remote, Joystick Keyboard, Mouse
Web viewer	Monitoring / Event / PTZ / Playback with IE
Java viewer	Monitoring / Event/ PTZ with IE, Chrome, Safari
Mobile viewer	Monitoring / PTZ / LogView with iPhone & Android
CMS	Control Center Standard, Max. 1024 DVRs
SDK	ActiveX(COM) SDK
Dimension	11.4(W) x 9.1(D) x 2.6(H) inch
Weight	5.5 lb (No HDD)
Operating temperature	5°C~45°C (41°F ~ 113°F)
Power	DC24V, 5A
Power consumption	Max. 30W Typical 20W
Approval	KC, FCC, CE, RoHS, HDcctv