HVRM-HSC1601F-D



FEATURES

Full HD Penta-Brid Video Recorder

- 16ch Standalone DVR supporting multi-video input
- Supports diverse video standards
- Digital : HD1080p, HD720p, DoubleReachTM
- Analog : Analog, 960H (NTSC/PAL)
- Built-in DoubleReachTM receiver function for all channels
- (Supports up to 400m HD video transmission without repeater)
- Up to 30fps(25fps) recording and playback per channel
- Adjustable recording quality and framerate per channel
- High-resolutions over 1200TVL at Live/Playback for HD1080p and DoubleReachTM video input
- Supports Dual Codec(H.264,JPEG) & Multi Stream
- HDMI, VGA, BNC video output
- HDMI & VGA : 1920 x 1080 video output
- BNC : CVBS. User-defined display & Alarm spot monitor support
- Various Live and Playback display (1/4/9/10/13/16 Split-screen)
- Robust IPFR (Intelligent Power Failure Recovery) DVR File System
- Max. 2 Internal SATA Type HDDs
- Max. 32TB(e-SATA) external storage interface
- Date/Time, Calendar/Time-line, Event, Thumbnail(Time Interval), Text Search available
- At-the-PC Playback of removed DVR HDD
- Lightning arresters on Video input, RS-485, DIO ports
- Provides bundle CMS program, managing Max. 1,024 DVRs in various ways such as E-map, Viewset
- Java Viewer for Chrome, Firefox, Safari

- Supports various mobile platform (iPhone/Android Viewer)
- Provides Full SDK for easy and powerful customization