

# HVRM-HTC410H



## FEATURES

Multi-Input HD DVR supporting HD-TVI & Analog Video

- H.264 & JPEG video compression
- Support both HD-TVI and analog cameras with adaptive access
- Supports up to 30fps @ 720P TVI camera
- Up to 30fps (25fps) recording and playback per channel
- HDMI and VGA output at up to 1920 x 1080P resolution
- Max 1 Internal SATA HDD (up to 6TB)
- JAVA Viewer for Chrome, Firefox, Safari, Mac OS X
- Provides Full SDK for easy and powerful customization.

Specifications	
Model Number	HVRM-HTC410H
Video compression	H.264 / JPEG
Analog and HD-TVI video input	4 ch, BNC interface (1.0Vp-p, 75Ω)
Supported camera types	1080p / 720p / Analog 960H/SD
Audio compression	G.711u
Video Output	1 HDMI, 1 VGA
HDMI / VGA output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Frame Rate	Max. 30fps per channel
Video bitrate	8Mbps
Audio In/out	1 RCA input/HDMI & RCA output
Audio bitrate	32 Kbps

<b>Specifications</b>	
Dual-stream	Support
Stream type	Video, Video & Audio
Playback resolution	Max. 30fps per channel @720P
Network protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
SATA	1 SATA interfaces
Network interface	1; 10M / 100M self-adaptive Ethernet interface
Serial interface	1; standard RS-485 serial interface
USB port	2 × USB2.0
Text Input	POS/ATM support, AVE VSI Pro/Hydra support
Power suppl	12V DC/3A
Consumption (without hard disks)	Max 9W(without HDD)
Working temperature	5 °C ~45 °C (41 °F ~ 113 °F)
Working humidity	10% ~ 90%
Dimensions (W × D × H)	300 (W) × 270(D) × 58 (H) mm (11.81 × 10.62 × 2.28 inch)
Weight (without hard disks)	3lbs (No HDD)