



MNR7508-GW



FEATURES

8 CH IP Mobile DVR

- User-friendly GUI providing easy and flexible operation.
- Supports 8 IP Cameras through PoE ports on back.
- 8 IP channels of audio & video inputs (depending on the camera used); each channel supports up to 1080p resolution with H.264 encoding technology.
- Two HDD/SSD with 1T capacity can be installed for data storage.
- Ignition start, delay (0 to 6h) shutdown and 24-hour scheduled startup/shutdown.
- Software-based firewall.

| Specifications | |
|---------------------|---|
| Model Number | MNR7508/GW |
| Video compression | H.264 |
| IP Video input | 8-ch PoE supported, incoming bandwidth 160Mbps |
| 2 way audio | 1/1 |
| Encoding resolution | Main stream: 1080p/720p/WD1/4CIF/CIF; Sub-Stream: CIF/QCIF |
| Frame rate | 1 to 30fps |
| Audio Output | 3-ch Aviation plug |
| Audio compression | G.711 |
| Video Out | 1 VGA, 3 Aviation plug |
| Dual stream | Supported |
| HDD Type | 2 × 2.5 inch hard disk (HDD/SSD) |
| HDD Capacity | Up to 1TB each |

| Specifications | |
|----------------------------|--|
| Two-way audio | G.722 |
| Network | 3G |
| Alarm input | 7-ch high/low level signal input |
| Alarm output | 2-ch relay signal output, 3mm connector |
| Network interface | 1 × 10M/100M self-adaptive RJ45 Ethernet interface |
| Serial interface | 1 × RS-232, 1 × RS-422 |
| USB port | 1 × standard USB 2.0 in front panel; |
| eSata | 1 |
| Sim Card | 2 standard sim card slots |
| Operating System | Linux |
| Power supply | Input: 8 to 36 VDC; Output: 12 VDC/2 A, 5 VDC/1 A |
| Consumption | ≤ 20 W (without IP camera or HDD) |
| Working temperature | -10° C to +55° C (14° F to 131° F) |
| Working humidity | 10% to 90% |
| Dimensions (W×D×H) | 9.7" x 8" x 3.5" |
| Weight (without HDDs/SSDs) | Approx. 3.3 kg (7.3lb) |