NS04R



FEATURES

HD-CCTV External Storage Equipment

- works with HVRM-HD1600F-PDR, HVRM-HD1600M-PDR, HVRM-HD1600F, HVRM1600F-R
- Dedicated storage equipment for DVR
- Supports WEBGATE's HD DVR series
- Max. 128TB storage expansion
- RAID Level 1/5/10 and support Auto-Rebuiding
- IPFR (Intelligent Power Failure Recovery) file system
- At-the-PC Playback of removed DVR HDD
- 4 Hot-Swap, SATA type HDD bays
- Built-in 1 network port for DVR connection
- Built-in 1 network port for NS04R cascade connection

NS04R
Embedded linux
4 SATA interface with hot-swap function
4 SATA interface with hot-swap function
Max. 32TB
Max. 128TB by cascaded NS04R, Max. 8 NS04R can be cascated
96MB/s
RAID level 1/5/10 with Auto Rebuild
Gigabit Ethernet for DVR connection
Gigabit ethernet for cascaded connection of NS04R

Specifications	
Dimension	445(W) x 383(D) x 44(H) mm
Weight	Approx. 5.5 Kg (with one HDD)
Operating temperature	5°C~45°C (41°F ~ 113°F)
Power	AC free voltage (100 ~ 240V), 50/60Hz
Power consumption	Max. 85W Typical 60W
Approval	CC, CE, KC, RoHS