

B/W BOARD CAMERA

HTC-250

SPECIFICATIONS

ITEMS	HTC-250
PICK UP DEVICE	1/3" CCD IMAGE SENSOR
PICTURE ELEMENTS H * V	EIA:510 * 492 - CCIR:500 * 582
HORIZONTAL RESOLUTION	More than 420 Lines
HORIZ. SYNC.FREQUENCY	EIA:15.734kHz. - CCIR:15.625 kHz
VERTICAL FREQUENCY	EIA:59.94Hz - CCIR:50Hz
SCANNING SYSTEM	2:1 INTERLACE
SENSITIVITY	0.01 Lux F=2.0
SYNCHORIZATION	Internal
S/N RATIO	more than 48 dB
ELECTRONIC SHUTTER	Up TO 1/100,000 sec. (Linear)
MOLUNT LENS	3.6mm F2.0
GAMMA	0.45
VIDEO OUTPUT	1 Vpp,75 Ohms
POWER SUPPLY	12 VDC (+/- 10%)
POWER CONSUMPTION	115 mA
WEIGHT gr	15
STORAGE TEMPERATURE	-30 to + 60 Degree C
OPERATING TEMPERATURE	-10 to + 50 Degree C

*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Dimensions & Connector

